


05.393.00..0000

## SANIT WC control 2 cables battery



Item number	Product description
05.393.00..0000	<p>WC control system, 2-cable, for accessible construction as per DIN 18040 finishing set with 6V DC battery</p> <p>WC flush system for manual remote flush actuation via two arm support rails with electric push button (with wire connection) or with an electric push button provided by the customer, for concealed cisterns with small access opening (from year of construction 2014) CC-121-S-FO-2V-2C, CC-122-S-UO-2V-2C and CC-150-S-UO-2V-2C</p> <p>Contents:</p> <ul style="list-style-type: none"> <li>- low-voltage motor for lifting device and control electronics with bracket</li> <li>- 2 cables 2.1 m long for two floating inputs with 2 luster terminals</li> <li>- 2 empty pipes 1.7 m long</li> <li>- Y-plug</li> <li>- battery compartment 6V DC</li> </ul> <p>Parameters:</p> <ul style="list-style-type: none"> <li>- automatic interval flush factory setting 24 h</li> </ul> <p>Settings on the low-voltage motor can be adjusted via the service and maintenance remote control DO-5.1 S*): 0-108 h intervall flush after last electronic flush</p> <ul style="list-style-type: none"> <li>- manual single flush also possible</li> <li>- flush volumes from 4.5-9 l, depending on the concealed cistern model</li> <li>- with error-safe plug connections</li> </ul> <p>Accessories:</p> <ul style="list-style-type: none"> <li>- service and maintenance remote control code no. 03.806.00..0000</li> </ul>