

05.392.00..0000

SANIT WC control 2 cables mains supply



Item number	Product description
05.392.00..0000	WC control system, 2-cable, for accessible construction as per DIN 18040 finishing set with mains supply 230V AC/6V DC WC flush system for manual remote flush actuation via two arm support rails with electric push button (with wire connection) or with an electric push button provided by the customer, for concealed cisterns with small WC control system, 2-cable, for accessible construction as per DIN 18040 access opening (from year of construction 2014) CC-121-S-FO-2V-2C, CC-122-S-UO-2V-2C and CC-150-S-UO-2V-2C Contents: - low-voltage motor for lifting device and control electronics with bracket - 2 cables 2.1 m long for two floating inputs with 2 luster terminals - 2 empty pipes 1.7 m long - Y-plug - power supply 230V AC/6V DC Parameters: - automatic interval flush factory set to 24h Settings on low-voltage motor can be adjusted via service and maintenance remote control DO-5.1 S*): 0-108 h interval flush after last electronic flush - manual single flush also possible - flush volumes from 4.5-9 l, depending on the concealed cistern model - with error-safe plug connection - power supply for installation outside the concealed cistern - designed for a maximum distance of 1.7 m between the concealed cistern and the power supply unit *) to be ordered separately Accessories: - concealed installation module code no. 03.933.00..0000 - service and maintenance remote control code no. 03.806.00..0000