

05.391.00..0000

SANIT WC control encoded radio signal battery



Item number

05.391.00..0000

Product description

WC control system using encoded radio signals for accessible construction as per DIN 18040

Finishing set with 6V DC battery

WC flush system for manual remote flush actuation via arm supports with wireless push button, for concealed cisterns with small access opening (from year of construction 2014) CC-121-S-FO-2V-2C, CC-122-S-UO-2V-2C and CC-150-S-UO-2V-2C

Contents:

- low-voltage motor for lifting device and control electronics with bracket
- radio receiver module
- battery compartment 6V DC

Parameters:

- automatic interval flush factory set to 24 h
- loading output, power rating 42V/0.5 A, pulse duration 0.5 sec.
- connection with up to 32 radio transmitters possible
- manual single flush also possible
- flush volumes from 4.5-9 l depending on the concealed cistern model
- with error-safe plug connections

Settings on low-voltage motor can be adjusted via service and maintenance remote control DO-5.1 S*): 0-108 h interval flush after last electronic flush

- frequency: 868.4 MHz (ISM range, no registration required, not subject to fees)
- transmission security by means of an automatic encoding procedure
- power output: < 5 mW, range 10 m, ambient temperature -20°C to 65°C
- radio receiver module with additional output for freely definable function *) to be ordered separately

Accessories:

- radio transmitter code no. 03.162.00..0000
- service and maintenance remote control code no. 03.806.00..0000