

90.744.00..T000

SANIT WC element INEO PLUS disabled 1120/450



Item number

90.744.00..T000

Product description

WC element INEO PLUS, handicapped accessible equipped with INEO FRESH box for water box cube, with small access opening, for wall-hung WC with mounting distance 180/230 mm, front-operated, h/w/d: 1,120/450/130 mm, WC mounted 50 mm higher than the standard height, for wall-hung WCs with an overhang > 60 cm, self-supporting powder-coated steel frame, for covering with plasterboard, installation onto a solid wall, in drywall constructions etc., 4-point-fastening, fully pre-assembled, includes self-locking feet with swivel base plates and fastening set, adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200 mm, adjustment range front to wall: 135-205 mm (when mounted on wall brackets code no. 17.257.00..T000), with back-to-back installation distance between front edges 270-310 mm, with SANIT double bend, SANIT concealed cistern with insulation against condensation (CC-121-S-FO-2V-2C), with dual flush (7.5-4.5 l/ 4-2 l) and flexible cable technology, factory setting 6 and 3 litres, with protection cap for the flush pipe, SANIT fill valve Noise Class I, 2-part angle valve connection set R 1/2, 4-position adjustable mounting clip, WC connection bend 90° DN 90 (d:90) with reducing sleeve DN 90(d:90)/DN 100(d:110) with protection cap, SANIT complete WC connection set DN 90(d:90)/180 mm, protection box for access opening and ceramic fittings can be cut to size, flexible hose to fill valve, can be screwed by hand, 2 M12 WC retaining bolts, incl. templates for transferring the access openings to the cladding panel, mounting material, protection plug and installation instructions, packed in a box

Concealed cistern tested to DIN EN 14055, Noise Class I

The cleaning cubes being used must be suitable for WC plastic cisterns and must not contain chlorine or any oxidizing components, otherwise the cistern may be damaged (e.g. stress cracking).

Accessories:

- fastenings (wall brackets, feet, bottom wall bracket)
- WC flush actuators
- sound-absorbing sets
- WC connectors (double bend, offset connection bend, etc.)
- cladding panel code no. 17.115.00..S000
- roughing-in set for shower toilet code no. 03.956.00..0000
- adjustable flush reducer code no. 05.261.00..0000