



SANIT Cistern 926 pneumatic 1V white



Item number

91.910.01..0000

Product description

Low-level for in-wall installation, flush volume adjustable from 6-9 I, factory set to 6 I, fully insulated, 3-side connection and low noise fill valve, cistern dimensions w/h/d: 442 x 366 x 150 mm, distance middle water inlet cistern/middle flush pipe outlet 485 mm, fixation of cistern middle/middle 240 mm, flush pipe length from upper edge of wall to end of flush pipe 155-263 mm, consisting of: cistern 926, angle valve G 1/2 and chromed connection pipe, flush pipe bend with rubber joint, pneumatic single flush WC push button, plastic, white, for brick and dry wall installation, w/h 120 x 114 mm, height above tiles 31 mm, minimum installation depth from wall covering to back of roughing in box 65 mm, with pneumatic push

Cistern 926 with WC push button, single flush, for remote pneumatic flush actuation

above tiles 31 mm, minimum installation depth from wall covering to back of roughing-in box 65 mm, with pneumatic push button unit, single flush pneumatic lift device, roughing-in box with protection box, single flush pneumatic hose – 2.35 m, empty pipe set with 1.7 m pull cord, installation instructions and fastenings, packed in a box An additional flush operation by the push button integrated in the cistern cover is not possible.

Accessories for flush pipe extension:

- extension pipe