

14.A00.01..0250

## SANIT right-angled grating 250 mm white



### Item number

14.A00.01..0250

### Product description

Thanks to their surface profile our gratings provide best non-slip properties, the non-slip characteristics laid down were exceeded by a clear margin, the water is returned perfectly fine into the overflow channel. The solid ribs are made of high impact-proof plastic with excellent ageing resistance, the material is fully recyclable. The individual elements of the right-angled ribbed gratings are connected into the maximum length of 1000 mm by tie rods of V4A stainless steel. The compact construction ensures fast installation and easy handling that makes for simple cleaning of the overflow channels. Our gratings are extremely stable and hard-wearing, non-rattling, weather proof, heat proof and resistant to chemicals and ultraviolet light. Suitable for a temperature range of between -30°C and +80°C. They possess good electrical antistatic characteristics and high resistance to sea, chlorine and healing waters. The solid ribs are designed for safety and cannot be broken when stamped upon, even if on purpose. The point loading factor per rib is at least 75 kg.

Variable widths of between 100 and 450 mm.

Up to 350 mm width, the rib height is 25 mm and over 350 mm width the rib height is 35 mm. The rib height can be matched to the height of the overflow channel.

Standard length: 1000 mm, intermediate lengths can be delivered if required.

Rib width: 12 mm

Rib spacing: 8 mm

The corners manufactured in mitre form make the range perfect: 90 degree inside and outside corners, special corners available in all angles. Our curved gratings offer a large variety of design options. We can manufacture the most diverse radii to match any shapes of pools and whirlpools.

Colours: light grey (RAL 7032), white (RAL 9016), other colours on request

Test mark: Tested according to DIN 51097 by Säurefließner-Vereinigung e.V. and placed in class "C", the highest evaluation possible with regard to non-slip safety.