



INEO FronTop 820/985 WC elements

Create space for your design ideas



TECHNOLOGY & INNOVATION

WWW.SANIT.COM

INEO FronTop 820/985 WC elements

Product profile

More space for grooming and wellness, more shelf space for bathroom utensils and decorations: Our INEO WC elements provide space for your creative ideas when it comes to bathroom design. They are ideally suited for low installation heights, recesses, roof slopes, small rooms and window understructures. Benefit from tested quality Made in Germany.

Advantages at a glance

Flexible use as needed

- Actuation from the front or top
- Small inspection opening, can be selected reversibly

Easy to install and space-saving

- Self-locking feet and adjustable footplates
- Compact concealed cistern
- Incorporation into INEO dry construction system 996 and lightweight single plank walls

Practical benefit of attractive design

- Elegant actuator plates of the Redonda, Linea and Creativa design lines, flush installation feasible
- Dual flush system to save water

Multiple connections

- New corner valve set for water connection to be mounted from outside
- Connection from the rear and laterally also possible
- Shower toilet can be connected
- Drain set for multifunctional flush release, with flexible cable system

Product description

with small access opening, front/top operated
h/w/d: 820/525/155 mm (height 820 pre-assembled for top operation, height 985 pre-assembled for front operation), self-supporting, powder-coated steel frame, for covering with plasterboard, installation onto a solid wall, in drywall constructions etc., 4-point fastening, fully pre-assembled, includes self-locking feet with swivel base plates and fastening set, adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200 mm, adjustment range front to wall: 155-205 mm (when mounted on wall brackets code no. 17.257.00..T000), SANIT concealed cistern with insulation against condensation (CC-122-S-UO-2V-2C) with dual flush (6 l/4-2 l), with protection cap for the flush pipe, SANIT fill valve Noise Class I, angle valve R 1/2, 4-position adjustable mounting clip, WC connecting bend 90° DN 90 (ø:90)/DN 100 (ø:110) with protection cap, SANIT complete WC connection set DN 90 (ø:90)/180mm, protection box for access opening can be cut to size, flexible hose to fill valve, can be screwed by hand, 2 M12 WC retaining bolts adjustable to 180/230 mm with protection plugs and nuts, installation instructions, without push plate, individually boxed

Test marks for concealed cistern: Noise Class I, tested to DIN EN 14055

Size	Code-no.
1. H/B/T: 820/525/155 mm	90.737.00..T000
2. H/B/T: 985/525/155 mm	90.738.00..T000

