

INEO PRE-WALL ELEMENTS INSTALLATION WITH SYSTEM





INSTALLATION WITH SYSTEM INEO PRE-WALL ELEMENTS

- Decades of experience in product design and manufacture, closeness to customers and service take center stage
- __ Modern bathroom design, high-quality unit of technology and design
- Perfect for any building situation
- __ In new buildings and for refurbishments in public, semi-public and private areas
- __ Innovative and flexible products, tested technology made in Germany
- __ Clever, custom-tailored solutions for a quick and simple installation
- Sustainability: water-saving, environmentally friendly flushing system

More than simply details: INEO BRIGHT flush plates for WC and urinal.





<u>04</u>


INNOVATIVE, FLEXIBLE SOLUTIONS

SYSTEM, DRYWALL AND BRICK WALL CONSTRUCTION

- __ Installation: in front of solid wall, in INEO PROFIL installation systems, using the INEO 996 drywall system, in lightweight studded wall and for individual extension
- Pre-wall elements for sanitary objects, standard elements and object-related elements with special fittings
- Rugged self-supporting elements, for dry cladding using commercially available cover panels
- __ Range of various construction heights
- __ WC installation elements for brick wall construction
- Short installation times: completely preassembled including fastening material
- __ Flush plates of various designs, high-quality material and colours
- Flushing either by hand or infrared control system by cable or radio actuation







Pre-wall installation: modular, innovative and sustainable.





FLUSHING SYSTEMS ARE OUR CORE COMPETENCE

NEW GENERATION OF INEO CONCEALED CISTERNS

- __ Heart of the WC elements, for almost all applications __ Installation-friendly connection of flush plate by
- __ Great functionality, mature technology
- Water-saving dual flush technique, flush volume adjustable by the universal flush valve
- __ Installation-friendly connection of flush plate by a flexible cable system, no adjustments required
- __ Universal fill valve 510, compact design, universally usable, high flow rate, super low noise
- Adjustable flush reducer, ideal solution for a modern WC, in particular suitable for rimless WCs
- Basic adjustments are made through the inspection opening with no need to remove the interior elements
- __ Time-tested technology, Noise Class I, in compliance with national and international norms
- 25 years spare parts guarantee for functional components



INEO FRESH box for water box cubes: Freshness and cleanliness for every flush



Video INEO FRESH box



Thanks to the easily adjustable flush reducer the flush can be regulated optimally.



Video adjustable flush reducer






MANUAL RELEASE OR CONTACTLESS UNIVERSALLY WITH INEO CONCEALED CISTERNS

- Flush plates multiple versions for customized bathroom design, clear design language, latest flush technology, high-quality materials, attractive range of colours
- Manual flush various designs and a multitude of colours
- Electronic release Flush plate SCOP featuring a functional lighting and backlight
- __ Infrared control contactless and hygienic flush release
- Flush release via coded radio signal, cable or remote pneumatic release

SANIT flush plates: timeless design with clear function.









OPTIMIZED DETAILS-RELIABLE-SUSTAINABLE-EASY TO INSTALL

NEW GENERATION PRE-WALL INSTALLATION INEO

For all building situations

08

- __ Installation in front of solid wall, in dry-wall construction or INEO 996 drywall system
- __ WC elements of various installation heights (1,120, 985, 820 mm)
- __ Small access opening, front or top operated

- __ Pre-assembled elements incl. connection kit for WC d: 90 mm
- Concealed cistern: water-saving dual-flush system, fill valve extremely quiet, flush volume infinitely variable







Simple element installation

- Rugged, self-supporting structure with 4 fixing points
- __ Self-locking feet with swivel base plates
- __ Suitable for installation in U-sections UW50, UW75 and SANIT rail system 996










PERFECTION IN DETAIL

NEW GENERATION PRE-WALL INSTALLATION INEO

New features

- Protective box for access opening can be shortened (1)
- Self-adhesive templates for transferring the access openings onto the cladding panel (1+2)
- Possible connection facility of electronic flush release (3)
- __ WC fastening 180/230 mm (3)
- __ Connecting bend clamp with depth adjustment and support fixing (4)
- __ Revision box as effective moisture protection and comfortable interface to shower toilet connection (5)



ELABORATE DETAIL WC ELEMENT INEO

Everything thought of - connections for shower toilet and electronic flush plates

- Prepared connections for empty pipesInstallation of water and electric connection easily possible
- __ Assembly of commercially available shower toilets





NO OBSTACLES - THE BARRIER-FREE BATHROOM

SUITABLE SOLUTIONS FOR WC AND WASHBASIN

For private and public use (in particular care facilities and hospitals)

WC area

- __ WC element INEO PLUS handicapped accessible, WC fastening 50 mm higher than the SANIT standard element
- __ WC control coded radio signal or WC control by 2 cables
- __ For barrier-free building according to DIN 18040, network or battery operation retrofittable
- Optional release mechanically, pneumatically, electronically via remote button or completely contactless

Washbasin area

- __ INEO washbasin frame to fit the needs of the disabled incl. wall-mounted odor trap height-adjustable DN 50/ DN 40
- Prefab kit with drain valve 1¼", connecting bend chromium-plated brass and cover white, chromium or stainless steel as alternatives

Supplementary items

- __ Fastening elements for fixing handles and supports with waterproof multiply laminated plywood panel
- __ Universally height adjustable, right or left design







VERSATILE USE

WASHBASIN ELEMENT INEO

INEO washbasin element

- __ Standard elements of various installation heights (1,120, 985, 820 mm)
- __ Universal use for washbasins and hand-washing basins
- __ For single-hole mixers or exposed wall-mounted mixers
- __ Elements pre-assembled incl. waste bend DN 50 / DN 40
- __ Cross beams variably adjustable
- With multiply laminated plywood panel and scaling for the free positioning of drinking water pipe wall plates








Plastic brackets for easier height adjustment and better sound decoupling

Insertion option for a cross beam (C-profile) as additional counter support




Plastic clip with depth fixation of the siphon bend for easy installation without tools

Washbasin elements with special features

- __ Element with 2 concealed water meter units
- Element for concealed installation of compressionproof small flow-type heaters







FOR ANY FLUSHING SYSTEM URINAL ELEMENT INEO



- __ Standard elements installation height 1,120 mm
- __ For urinal cartridge valve technology
- __ Universally adjustable on various urinal ceramics
- Urinal roughing-in box with fully revisable water section, including integrated stop valve and filter (incl. factory leak test)
- Flow-optimized urinal suction odor trap, optimal flushing
- Flush release by mechanical, hand-operated, pneumatic cartridge valve, high-quality urinal cover plates (different designs, materials, colours, flush-mounted installation possible)
- Flush release electronically, cartridge solenoid valve 6V DC
- __ Contactless, infrared sensor-controlled flush release, battery, mains supply or series systems
- __ Vandal-proof, invisible, contactless, conductively controlled RL1 technology (relative conductivity), voltage supply: mains supply or series systems
- Parameterization through maintenance and service remote control

Manual operation system



Infrared



RL1



Video urinal element INEO







SPECIAL APPLICATIONS

SPECIAL ELEMENTS INEO

WC element INEO

For floor standing toilet, floor standing toilet for children and toddlers

- __ Flush volume adjustable on ceramics
- __ Condensation water insulated SANIT concealed cistern with dual flush
- Concealed cistern can be adjusted to operating heights of children and toddlers

WC element INEO PLUS 450 with air-admittance valve set ventilair DN 30-50

- __ Minimizes effort for installation and maintenance
- __ No wall mounting box required
- __ Easily removable through access opening
- __ System tested and monitored according to DIN EN 12380
- __ Type class A I, flow rate 8 L/s

WC corner element 995 SC

- For wall-hung WC with mounting distance of 180/230 mm
- __ Max. 6 fixing points
- __ One-sided wall mounting possible
- Condensation water insulated SANIT concealed cistern with dual flush

Urinal element INEO for exposed flush valves or for ceramic urinals with integrated controls

- $_$ With 1 sound-insulated wall bushing G 1/2 internal thread / G 1/2 male thread
- With 2 urinal fastening bolts M8 including protective system and covers
- With drain connecting bend DN 50 (d: 50) and soundabsorbing clamp











Bidet element INEO

- __ Various installation heights (1,120, 985 and 820 mm)
- With multiply laminated plywood panel and scaling for the free positioning of water connections for various pipe systems by the customer
- With 2 retaining bolts M12 adjustable 180/230 mm, incl. protection plugs
- With universal drain connecting bend DN 50 (d: 50)/DN 40 (d: 40), incl. rubber sleeve DN 40 (d: 40)/DN 32 (d: 32), protection plug and noise-insulated waste bend clamp



Sink element INEO

- __ For wall-mounted mixers
- __ Adjustable by feet extended to 1,220 mm
- __ With noise-insulated pipe clamp incl. drain connecting bend DN 50
- __ Universally adjustable for sinks
- __ All cross beams pre-assembled



Concealed bath system frame INEO RIM

- Base frame next to a bath tub
- __ Seating of 3- and 4-hole fittings
- __ Self-supporting, free-standing
- __ Hose box incl. accessories to drain dripping water
- Tilable valve and fitting support with concealed fixation
- Water connections in hose box incl. angle valves for fitting connection





Modern technology for a perfect bathroom design.

NAME	HEIGHT WIDTH	FEATURES	CODE NO.
WC ELEMENT INEO PLUS 450 FOR WALL-HUNG WC	1,120 MM 450 MM	- WALL BRACKETS - ADJUSTABLE FLUSH REDUCER - INEO FRESH BOX - REVISION BOX WITH 2 EMPTY PIPES FOR CONNECTION POSSIBILITY FOR ELECTRONICAL RELEASE / SHOWER TOILET	90.743.005000
WC ELEMENT INEO PLUS 450 FOR WALL-HUNG WC	1,120 MM 450 MM	- WALL BRACKETS - INEO FRESH BOX - REVISION BOX FOR WC CONNECTION	90.743.005011
WC ELEMENT INEO PLUS 450 FOR WALL-HUNG WC	1,120 MM 450 MM	- INEO FRESH BOX - REVISION BOX FOR WC CONNECTION	90.743.005020
WC ELEMENT INEO PLUS FOR WALL-HUNG WC	1,120 MM 450 MM	- HANDICAPPED ACCESSIBLE - WC MOUNTED 50 MM HIGHER THAN STANDARD HEIGHT - INEO FRESH BOX - REVISION BOX FOR WC CONNECTION	90.744.00T000
WC PACKAGE INEO PLUS 450 FOR WALL-HUNG WC	1,120 MM 450 MM	- COMPLETE SET FOR WC INSTALLATION - COMPRISING WC ELEMENT, FLUSH PLATE, THERMOSETTING PLASTIC WC SEAT, SOUND INSULATION SET AND WC PAN	90.775.000000
WC ELEMENT INEO PLUS FOR WALL-HUNG WC	1,120 MM 450 MM	- FREE-STANDING - WITH HEAVY-DUTY SUPPORT FEET	90.724.000000
WC ELEMENT INEO FRONTOP 820 FOR WALL-HUNG WC	820 MM 525 MM	- FRONT/TOP OPERATED - INEO FRESH BOX - REVISION BOX FOR WC CONNECTION	90.745.00T000
WC ELEMENT INEO FRONTOP 985 FOR WALL-HUNG WC	985 MM 525 MM	- FRONT/TOP OPERATED - INEO FRESH BOX	90.738.00T000

LIST OF PRODUCTS WC ELEMENTS INEO

NAME	HEIGHT WIDTH	FEATURES	CODE NO.
WC ELEMENT INEO PLUS 450 WITH AIR ADMITTANCE VALVE SET FOR WALL-HUNG WC	1,120 MM 450 MM	- WITH AIR ADMITTANCE VALVE SET VENTILAIR DN 30 -50 - WALL BRACKETS - REVISION BOX FOR WC CONNECTION	90.746.000000
WC ELEMENT INEO FOR FLOOR STANDING WC	1,120 MM 525 MM	- HEIGHT ADJUSTABLE CONCEALED CISTERN - FOR CHILDREN'S AND AND TODDLERS' FLOOR STANDING WC	90.735.00T000
WC CORNER ELEMENT 995 SC FOR WALL-HUNG WC	1,120 MM 370 MM	- FOR CERAMICS WITH MOUNTING DISTANCE 180/230 MM - DEPTH: 200 MM - MAXIMUM 6-POINT FASTENING	90.699.000000
EXCREMENT SINK ELEMENT INEO FOR WALL-HUNG WC	1,530 MM 525 MM	- FOR PUPLICA WALL-HUNG SINK - WITH TRAVERSE FOR EXPOSED MIXERS - STATIC LOADING CAPACITY OF UP TO 400 KG	90.659.000000
INEO SOLO SANITARY MODULE FOR WALL-HUNG WC	1,115 MM 450 MM	- CLADDING WHITE - CLADDING BLACK - WC ELEMENT WITH CLADDING, COVER AS WELL AS WC AND WATER CONNECTION SETS	90.730.000005 90.730.000008
WC ELEMENT INEO SCAN	1,120 MM 525 MM	- WITH WATER CONNECTION IN THE CISTERN - WITH 4 WALL BRACKETS FOR FLOORLESS MOUNTING - CAN BE UPGRADED FOR SHOWER TOILETS	90.736.000000

LIST OF PRODUCTS PRE-WALL INSTALLATION ELEMENTS

	NAME	HEIGHT WIDTH	FEATURES	CODE NO.
	WASHBASIN ELEMENT INEO	1,120 MM 525 MM	- FOR SINGLE HOLE MIXERS - WITH MULTIPLY LAMINATED PLYWOOD PANEL AND SCALING FOR FREE POSITIONING OF DRINKING WATER CONNECTIONS	90.696.00T000
		985 MM 525 MM		90.669.00T000
		820 MM 525 MM		90.672.00T000
	WASHBASIN ELEMENT INEO	1,120 MM 525 MM	- FOR SINGLE HOLE MIXERS - FOR CONCEALED INSTALLATION OF COMPRESSION-PROOF SMALL FLOW-TYPE HEATERS	90.689.00T000
	WASHBASIN ELEMENT INEO	1,120 MM 525 MM	- FOR SINGLE HOLE MIXERS - WITH 2 CONCEALED WATER METER UNITS, CONCEALED VALVE AND T-PIECE FOR	90.687.00T000
		985 MM 525 MM	ANGLE VALVE AND STOREY DISTRIBUTION	90.691.00T000
1	WASHBASIN ELEMENT INEO	1,120 MM 525 MM	- FOR EXPOSED WALL- MOUNTED MIXERS	90.671.00T000
	WASHBASIN ELEMENT INEO	1,120 MM 525 MM	- HANDICAPPED ACCESSIBLE - FOR SINGLE HOLE OR EXPOSED WALL-MOUNTED MIXERS	90.673.00T000
Ÿ		820 MM 525 MM		90.685.00T000
	URINAL ELEMENT INEO	1,120 MM 525 MM	- FOR URINAL CARTRIDGE VALVE TECHNOLOGY - WITH UNIVERSAL CARTRIDGE ROUGHING-IN SET AND URINAL EXHAUST TRAP	90.668.00T000
	URINAL ELEMENT INEO	1,120 MM 525 MM	- FOR EXPOSED FLUSH VALVES OR FOR CERAMIC URINALS WITH INTEGRATED CONTROLS - WITH SOUND-INSULATED WALL BUSHING AND SOUND-ABSORBING CLAMP	90.675.00T000


LIST OF PRODUCTS PRE-WALL INSTALLATION ELEMENTS

	NAME	HEIGHT WIDTH	FEATURES	CODE NO.
	BIDET ELEMENT INEO	1,120 MM 525 MM	- UNIVERSAL ADJUSTABLE TO BIDET CERAMICS - WITH MULTIPLY LAMINATED PLYWOOD PANEL AND SCALING FOR THE FREE POSITIONING OF DRINKING WATER CONNECTIONS FOR VARIOUS PIPE SYSTEMS	90.676.00T000
	BIDET ELEMENT INEO	985 MM 525 MM	- WITH UNIVERSAL DRAIN CONNECTING BEND DN 50 / DN 40 - WITH SOUND-ABSORBING WASTE BEND CLAMP	90.662.00T000
	BIDET ELEMENT INEO	820 MM 525 MM		90.663.00T000
	SINK ELEMENT INEO	1,120 MM 525 MM	- FOR WALL-MOUNTED MIXERS - WITH SOUND-ABSORBING CLAMP AND DRAIN CONNECTING BEND DN 50	90.677.00T000
	EMPTY FRAME INEO	1,120 MM 525 MM	- BASE ELEMENT FOR UNIVERSAL CONCEALED MODULES - ALSO SUITABLE FOR BRIDGING GAPS OF 550 TO 1,650 MM BETWEEN ELEMENTS	90.688.00T000
-	ELEMENT INEO FOR FIXING HANDLES AND SUPPORTS	1,120 MM 294 MM	- RIGHT VERSION - LEFT VERSION - FOR BARRIER-FREE EQUIPMENT - ALSO SUITABLE FOR BRIDGING GAPS OF 500 TO 1,100 MM BETWEEN ELEMENTS	90.680.00TR00 90.680.00TL00
	BATH AND SHOWER TRAY ELEMENT INEO	1,120 MM 525 MM	- FOR EXPOSED WALL MIXERS	90.681.00T000
	BATH AND SHOWER TRAY ELEMENT INEO	1,120 MM 525 MM	- FOR CONCEALED MIXERS	90.682.00T000
00.	CONCEALED BATH SYSTEM FRAME INEO RIM	500 MM 675 MM	- BASE FRAME NEXT TO A BATH TUB - TO BE TILED AND TO INTEGRATE 3-4 VALVES AND FITTINGS	90.686.000000





Video of SANIT rail system 996





CUSTOMIZED ROOM DESIGN INEO 996 DRYWALL SYSTEM

- For every building situation the perfect room design (family bathroom, guest toilet, barrier-free bathroom design)
- __ New or modernization
- __ Customized room design half-height and floor-to-ceiling walls,) partition walls, special solutions (niches, racks, roof pitches)
- __ Implementation of complex and demanding designs
- __ Cost-saving little installation effort and easy to store
- Rugged, self-supporting structure with few component parts, can be combined with pre-wall elements or modules for all sanitary objects
- __ Sound insulation tested according to DIN 4109
- _ Comprehensive service: advice, planning tool for material, costs and installation time

Flexible and time-saving











LIST OF PRODUCTS DRYWALL CONSTRUCTION SYSTEM 996

	NAME	CODE NO.
	DAII	02 208 00 0000
5 m	RAIL	02.208.000000
	RAIL FIXTURE	03.545.000000
	CORNER CONNECTOR	03.332.000000
200	TRANSPORT-MULTI-CORNER CONNECTOR	05.251.00.0000
	MULTI-CONNECTOR	03.803.000000
	MULTI-CONNECTOR 996 MAX. INSTALLATION WALL DEPTH 215 MM	03.723.000000
1	MULTI-CONNECTOR 996 MAX. INSTALLATION WALL DEPTH 315 MM	03.723.00S000
	BRACKET FOR MULTI-CONNECTOR	04.159.000000
	CONNECTION SET	03.754.000000
Pa	MODULE CONNECTOR	03.333.000000
	SUPPORT FOOT FOR FREE-STANDING WALLS	04.070.000000

LIST OF PRODUCTS DRYWALL CONSTRUCTION SYSTEM 996

	NAME	CODE NO.
	PIPE CLAMP MOUNTING M8	05.201.000000
	ROOF PITCH CONNECTION	05.132.000000
	MODULE FOR WATER CONNECTIONS	17.281.000000
	MODULE FOR WASHING MACHINE CONNECTION	17.282.000000
ACCESSORIES	INSULATION STRIP FOR PLASTER CONNECTION	03.346.000000
	PLASTERBOARD CLADDING PANEL H/W/D: 1,300 X 600 X 18 MM	17.115.005000
~	SCREWS FOR CLADDING PANEL	02.597.000000
	UNIVERSAL FILLER	02.596.000000

NAME	CODE NO.
WASHBASIN MODULE FOR SINGLE HOLE MIXERS W/D: 305 X 70 MM	17.286.000000
WASHBASIN MODULE FOR SINGLE HOLE MIXERS AND EXPOSED WALL-MOUNTED MIXERS W/D: 444 X 70 MM	17.276.000000
WASHBASIN MODULE, HANDICAPPED ACCESSIBLE W/D: 505 X 150 MM	17.288.000000
MODULE FOR WASHBASIN AND SINKS WITH EXPOSED MIXERS W/D: 444 X 70 MM	03.877.000000
MODULE FOR EXPOSED MIXERS W/H/D: 444 X 70 X 70 MM	17.275.000000
MODULE FOR CONCEALED OR EXPOSED MIXERS FOR WALL PLATES W/H/D: 444 / 120 / 98 MM	17.268.000000
MODULE FOR CONCEALED OR EXPOSED MIXERS FOR WALL PLATES W/H/D: 505 / 120 / 150 MM	17.287.000000
MODULE FOR KITCHEN CONNECTIONS W/D: 444 X 70 MM	17.280.000000

LIST OF PRODUCTS MODULES

NAME	CODE NO.
FIXING MODULE FOR HANDLES, HEAVY ITEMS, ETC. W/H/D: 444 / 125 / 30 MM	17.216.000000
MODULE FOR SEAT FIXATION W/H/D: 444 / 350 / 30 MM	17.239.000000
FIXING MODULE FOR HANDLE AND SUPPORT SYSTEMS W/H/D: 254 / 400 / 30 MM	17.279.000000
FIXING MODULE FOR HANDLE AND SUPPORT SYSTEMS W/H/D: 320 / 505 / 70 MM	17.289.000000



FAST AND CLEVER TO THE DESIRED RESULT INEO PROFIL INSTALLATION SYSTEMS

Plan safely, save time and money, benefit from excellent flexibility and quality. The INEO PROFIL installation systems are the right choice. We would be glad to give you advice on your building project.

STRONG POINTS

- __ Custom-tailored pre-assembled installation systems
- __ Use of standardized, high-quality products
- __ Cost-optimized by short installation times
- High reliability when it comes to planning, on-site measurement and delivery to site
- __ Optimal planning and calculation security

All information on the INEO PROFIL installation systems is available in our separate leaflet and on our website www.sanit.com.









CURIOUS TO KNOW MORE?

If you want to learn more about the INEO pre-wall installation, other products and services offered by us and this company visit www.sanit.com

SANITÄRTECHNIK EISENBERG GMBH

Gewerbegebiet – In der Wiesen 8 D-07607 Eisenberg

Postfach 1149 | D-07601 Eisenberg

T +49 (0) 36691 598-0 F +49 (0) 36691 598-88000

info@sanit.com

www.sanit.com

